

Miller 8183 Cross-Arm Anchorage Strap

Description

The 8183 Cross-Arm Strap wraps around I-beams and other structures and attaches with a 2-inch (50mm) D-ring that slips through a 3-inch (76mm) D-ring to form a secure attachment point for lanyards and other connecting devices.

Materials

Webbing: 2" (50mm) Polyester webbing
D-Rings: Steel; 2" (50mm) and 3" (76mm) diameter
Thread: Six-cord bonded, three-strand polyester thread.

Labels: Valeron

*All hardware meets ASTM (50) fifty-hour salt spray test requirements

Technical

Maximum Working

Load Capacity: 400 lbs (181.4 kg)
Webbing: 5,000 lbs (22 kN) minimum tensile strength
D-Rings: 5,000 lbs (22 kN) minimum tensile strength
Thread: 42 lbs (19 kg) minimum tensile strength
***Length:** 6 ft (1.8m) standard length
 *Additional lengths available



Certification

OSHA 1926.502, OSHA 1910.66, ANSI A10.32 and ANSI Z359-2007



LIMA

Cal. Huayucan 172 Coop. 27 de Abril - Ato

AREQUIPA

Cal. Las Orquídeas 204-206 Urb. Primavera - Yanahuara

LA LIBERTAD

Av Teodoro Valcárcel 784-786 - Trujillo

Central Telefonica

01 624 3435

ventas@imrecard.com