Heavy-Duty Welder Harnesses

Description

The Heavy-Duty Welder Harnesses are designed with rugged black Kevlar® webbing to withstand harsh welding environments. They meet ASTM F887 Arc Test requirements and are rated for arc exposure.

Materials

Webbing: 1-3/4" Kevlar Elastic Keepers: Kevlar, Elastic Kevlar, Polyester Thread (Stitching): Web Back D-Ring: Kevlar Webbing

*Metal Back D-Ring: Clear Chromate Finished Carbon Steel *Buckles: Clear Chromate Finished Carbon Steel

Grommets: Brass Labels: Valeron Connection Insulators: Leather

Back D-ring Pad

(ULTRA): Nylon, Polyester, Urethane;

Evoprene, Copolymer Polypropylene

Evoprene, Copolymer Polypropylene Back D-ring Pad:

Label Pack: Evoprene, Nylon

* All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Certification

Meets OSHA 1926.502, ANSI A10.32, Z359.1 and CSA requirements. Also meets ASTM F887 Arc Test requirements and are rated for arc exposure.



Technical

Max. Working Load: 400 lbs (181.4kg) Webbing Min. Tensile: 5,000 lbs (22kN) D-ring Min. Tensile: 5,000 lbs (22kN) Buckle Min. Tensile: 4,000 lbs (18kN)

ULTRA Models	Shoulder Strap	Chest Strap	Leg Straps	Front D-ring	Side D-rings	Back D-ring	Special Features
850KQC/UBK	Friction	Quick-Connect	Quick-Connect	Option	No	Web	Dull down adjustment
850KQC-4/UBK	Friction	Quick-Connect	Tongue	Option	No	Web	Pull-down adjustment; Leather insulators
850KQC-58/UBK	Friction	Quick-Connect	Tongue	Option	Yes	Web	
650KQC/UBK	Friction	Quick-Connect	Quick-Connect	Option	No	Web	
650KQC-4/UBK	Friction	Quick-Connect	Tongue	Option	No	Web	Pull-up adjustment;
650KQC-58/UBK	Friction	Quick-Connect	Tongue	Option	Yes	Web	Leather insulators
650KQC-7/UBK	Friction	Quick-Connect	Quick Connect	Option	Yes	Web	
650KQC-77/UBK	Friction	Quick-Connect	Tongue	Option	Yes	Web	Pull-up adjustment; Leather insulators; Removable Body Belt
Model No.	Shoulder Strap	Chest Strap	Leg Straps	Front D-ring	Side D-rings		Special Features
850K-4/UBK	Friction	Mating	Tongue	Option	No	Metal	Pull-down adjustment
650K-4/UBK	Friction	Mating	Tongue	Option	No	Metal	
650K-58/UBK	Friction	Mating	Tongue	Option	Yes	Metal	Pull-up adjustment; Belt loops
650K-7/UBK	Friction	Mating	Mating	Option	Yes	Metal	
650K-77/UBK	Friction	Mating	Tongue	Option	Yes	Metal	Pull-up adjustment; Belt loops; Removable Body Belt

Model numbers listed are for universal size (L/XL). Harnesses are also available in small/medium and XXIarge by replacing the "U" in the model number with "S/M" or "XXL" (Ex.850KQC/S/MBK). For front D-ring vest-style option, add "FD" to the corresponding harness SKU number (Ex.850KFDQC/UBK).

Toll Free 800.873.5242 (press 4)

hsptechsupport@honeywell.com • www.millerfallprotection.com

▲ WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.



